



Smeermiddelenindustrie • Schmiermittelindustrie

DE OLIEBRON LUBRICATION(GD) CO.,LTD

TEL: +86 4008801150

Internet: <http://www.deoliebron.com>

E-mail: info@deoliebron.com

Lube-oil industry • Industrie Lubrifiant

SynthTrans ATF 9G

Description

A very high graded, extremely low-viscosity automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives to obtain the following properties:

- excellent contribution to fuel economy
- excellent lubrication
- very good resistance against oxidation
- very good thermal stability
- excellent and very stable friction characteristics
- excellent resistance against corrosion and foaming
- excellent protection against wear
- a very high and stable viscosity index

Application

This premium synthetic product is specially formulated for the lubrication of certain Mercedes-Benz automatic transmissions with 9 gears. This oil contributes significantly to realizing fuel saving and can be used in automatic transmissions where an oil with the specification MB 236.17 is prescribed.

Specifications

Performance level:
MB 236.17

Typicals

Density at 20 °C, kg/l	0,836
Viscosity 40 °C, mm ² /s	17,22
Viscosity 100 °C, mm ² /s	4,5
Viscosity Index	190
Flash Point COC, °C	208
Pour Point, °C	-49

