



Smeermiddelenindustrie • Schmiermittelindustrie

DE OLIEBRON LUBRICATION(GD) CO.,LTD

TEL: +86 4008801150

Internet: <http://www.deoliebron.com>

E-mail: info@deoliebron.com

Lube-oil industry • Industrie Lubrifiant

SynthTech GF 5W30

Description

A modern, Fully synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to

obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

A fuel economy, special composed synthetic motor oil recommended for use in petrol engines of passenger cars, which prescribe an oil with the specification GM dexos1™ Gen 2.

Specifications

Resource Conserving

API SP ILSAC GF-6A

Meets the requirements of:

GM dexos1 (TM) Gen 2 GM 6094M;Chrysler MS 6395;

Ford WSS-M2C945-A/B1/946-A/B1/947-A/B1;

Ford WSS-M2C953-B1 Ford WSS-M2C946-A/B1 / WSS-M2C961-A1

Typicals

Density at 20 °C, kg/l	0,854
Viscosity -30 °C, mPa.s	5980
Viscosity 40 °C, mm²/s	67,07
Viscosity 100 °C, mm²/s	11,07
Viscosity Index	157
Flash Point COC, °C	234
Pour Point, °C	-42
Total Base Number, mgKOH/g	7,24
Sulphate Ash, %	0,72
HTHS viscosity@150, mPa.s	3,2