



Smeermiddelenindustrie • Schmiermittelindustrie

DE OLIEBRON LUBRICATION(GD) CO.,LTD

TEL: +86 4008801150

Internet: <http://www.deoliebron.com>

E-mail: info@deoliebron.com

Lube-oil industry • Industrie Lubrifiant

4T Motorcycle HS 5W40

Description

A new generation full-synthetic engine oil for four-stroke motorcycles formulated with synthetic base oils combined with special developed balanced additives to achieve the following properties:

- a high and stable viscosity index
- optimal friction characteristics
- a very strong protection against wear, corrosion and foaming
- a very good detergency and dispersion

Application

This oil is special developed for the lubrication of four-stroke motorcycles, so that sliding, sticking and/or rough changing of the clutch-plates no longer occurs. This oil is developed and tested in co-operation with the most important motorcycle producers and has its performance demonstrated in the field.

Specifications

Performance level:

API SN

JASO MA2

JASO MA

Typicals

Density at 20 °C, kg/l	0,852
Viscosity -30 °C, mPa.s	5901
Viscosity 40 °C, mm²/s	88,19
Viscosity 100 °C, mm²/s	14,01
Viscosity Index	167
Flash Point COC, °C	220
Pour Point, °C	-40
Total Base Number, mgKOH/g	4,68
Sulphate Ash, %	0,94

