## De Oliebron



## **Product Information NS-A.16.11**

Lube-oil industry • Industrie Lubrifiant

Smeermiddelenindustrie • Schmiermittelindustrie DE OLIEBRON LUBRICATION(GD) CO.,LTD TEL: +86 4008801150 Internet: http://www.deoliebron.com E-mail: info@deoliebron.com

Г

## Export Gear Oil 80W90 GL-5

Description	<ul> <li>This gear oil is a mineral lubricating oil for mechanical transmissions, formulated with high quality solvent refined base oils and special EP-additives to obtain the following properties:</li> <li>excellent resistance against oxidation</li> <li>a very high activity against wear, corrosion and foam</li> <li>a low pour point</li> <li>very good EP-properties</li> </ul>	
Application	This gear oil is used in hypoid differentials under very heavy duty conditions and should be used in all transmissions that require EP-transmission oils.	
Specifications	Performance level: API GL-5	
Typicals	Density at 20 °C, kg/l Viscosity 100 °C, mm²/s Viscosity Index Flash Point COC, °C Pour Point, °C	
11/29/2017	The data mentioned in this product information sheet are mea products. Although this overview is composed with all possibl	ant to enable the reader to orient himself about the properties and possible applications of our e carefulness on the stated date, the composer does not accept any liability for damages caused

products. Airdough this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. You can download a recent material safety data sheet of this product on our website..