



Product Information NS-A.12.27

Lube-oil industry • Industrie Lubrifiant

Smeermiddelenindustrie • Schmiermittelindustrie

DE OLIEBRON LUBRICATION(GD) CO.,LTD

TEL: +86 4008801150 Internet: http://www.deoliebron.com E-mail: info@deoliebron.com

4T Super 10W40

Description

Application

A fully synthetic engine oil for four stroke motor-cycles formulated with high quality synthetic base oils combined with balanced additives to achieve the following properties:

- a high and stable viscosity index
- good friction characteristics
- a strong protection against wear, corrosion and foaming
- a good detergency and dispersion

This oil is developed for the lubrication of four stroke motor-cycles, so that sliding, sticking and/or rough changing of the clutch-plates no longer occurs. This oil is developed and tested in co-operation with the motor cycle producers and has its performance demonstrated in the field.

Specifications

Typicals

Performance level: API SL

JASO MA2 JASO MA

Density at 15 °C, kg/l 0,846 Viscosity -25 °C, mPa.s 3879 Viscosity 40 °C, mm²/s 88,23 Viscosity 100 °C, mm²/s 13,92 Viscosity Index 162 Flash Point COC, °C 253 Pour Point, °C -42 Total Base Number, mgKOH/g 5,9

