



Smeermiddelenindustrie • Schmiermittelindustrie

Lube-oil industry • Industrie Lubrifiant

DE OLIEBRON LUBRICATION(GD) CO., LTD

12F, BUILDING 1, LIANDONG INTELLIGENT INDUSTRIAL PARK, 105

SHILONG NORTH ROAD, NANHAI DISTRICT, FOSHAN CITY, GUANGDONG

PROVINCE, CHINA

Tel. +86 400 880 1150

Internet: <http://www.deoliebron.com>

e-mail: info@deoliebron.com

Tor MT/LD Gear Oil 75W80

Description

This gear oil is a fully synthetic lubricating oil for mechanical transmissions, formulated with high quality synthetic base oils and special EP-additives to obtain the following properties:

- an excellent thermal stability
- a very high activity against wear, corrosion and foam
- a low pour point
- very high quality EP-properties
- good clutch-switch performance at low temperatures
- long durability
- fuel economy

Application

This gear oil is special developed for gearboxes under very heavy duty conditions together with high temperatures. This oil can also be used for extended drain intervals.

Specifications

API GL-4

MAN 341 Typ Z4

ZF TE-ML 01L/02L/16K

Meets the requirements of:

DAF

Eaton Europe (extended drain)

Iveco

Renault

Volvo 97307

ZF TE-ML 08/13

Typicals

Density at 15 °C, kg/l	0,858
Viscosity 40 °C, mm ² /s	59,50
Viscosity 100 °C, mm ² /s	10,00
Viscosity Index	155
Flash Point COC, °C	218
Pour Point, °C	-39

