



Smeermiddelenindustrie • Schmiermittelindustrie
 DE OLIEBRON LUBRICATION(GD) CO.,LTD
 TEL: +86 4008801150
 Internet: <http://www.deoliebron.com.cn>
 E-mail: info@deoliebron.com

Lube-oil industry • Industrie Lubrifiant

HyperSynth 5W40

Description

This full-synthetic fuel economy universal motor oil is produced with high quality solvent refined base oils and a number of additives, to obtain the following properties:

- a high detergency and dispersion power
- a strong resistance against oxidation
- effective in preventing from wear, corrosion and foam
- a high and stable viscosity index

Application

Suitable lubricating oil for gasoline engines under light service conditions, moreover for diesel engines of passenger cars and for light delivery vans in light service. Not applicable for turbo-charging diesel engines for which a minimum API CG level oil is required.

Specifications

Performance level:
 API SP
 ACEA A3/B4
 VW502.00 AND 505.00
 MB229.3
 BMW LONGLIFE 01

Typicals

Density at 20 °C, kg/l	0,848
Viscosity -30 °C, mPa.s	5950
Viscosity 40 °C, mm ² /s	88,27
Viscosity 100 °C, mm ² /s	13,84
Viscosity Index	158
Flash Point COC, °C	238
Pour Point, °C	-42
Total Base Number, mgKOH/g	7,2
Sulphate Ash, %	--

